

TELESCOPIC HOT STICKS



TEL-O-POLE II/ THE "NO TWIST" STICK (Patent Pending)

NEW! TEL-O-POLE II, THE "NO TWIST" STICK. A unique triangular design by Hasting Fiberglass, the originators of Telescoping Hot Sticks. All models are heavy duty designed.

FEATURES AND BENEFITS

- **TRIANGLE SHAPE** - Enables each section to "Lock In automatically." No more twisting and turning to lock sections.
- **HIGH VISIBILITY** - Fluorescent tip section is highly visible and has a foam core. All tip sections are 1.15" diameter. All sections are 100% tested per OSHA and ASTM F-711.
- **EXTRA REACH** - New 40' model now available.
- **RE-DESIGNED LOCK BUTTONS** - New shape and larger size are easier to operate with and without gloves.
- **MORE VERSATILE** - Use only the number of required sections to perform each job, Example: A 40 ft. (12.2 Meters) tool can be reduced to a 20 ft. (6.1 Meters) working height by depressing the lock button and sliding the bottom sections off. This allows for a lightweight tool to perform the work easier.
- **EASY DISASSEMBLY** - Simply depress the lock button and slide section, or sections, out. No tools are required for disassembly.
- **ERGONOMIC DESIGN** - Gives the operator a "better gripping" surface for better control
- **REDUCES INVENTORY** - Only one size lock button and spring for replacement needs.
- **EASY MAINTENANCE** - All sections have a smooth glossy surface for routine cleaning and waxing.
- **NEW BASE CAP** - Cushions and protects base end.
- **IMPROVED UNIVERSAL HEAD** - Strong aluminum alloy head incorporates corona discharge design and "includes a captive Belleville washer" to hold universal attachments securely.



End view showing
Triangular shape



(Actual Size)
Locking Button
Top View



Locking Button
Side View

ORDERING INFORMATION

CAT. NO.	EXTENDED LENGTH (NOMINAL)	RETRACTED LENGTH	BASE DIA.	WT.	STORAGE CASE / P/N
HV-208*	8' (2.43 m)	26" (67 cm)	1.75"	3.0 lbs. (1.4 kg)	C-208
HV-212	127" (3.8 m)	58" (1.48 m)	1.45"	3.7 lbs. (1.66 kg)	C-30
HV-216	169" (5.0 m)	60" (1.53 m)	1.61"	5.0 lbs. (2.26 kg)	C-30
HV-220	21' (6.43 m)	62" (1.58 m)	1.75"	6.4 lbs. (2.92 kg)	C-30
HV-225	25'6" (7.8 m)	64" (1.63 m)	1.91"	8.1 lbs. (3.68 kg)	C-40
HV-230	30' (9.21 m)	66" (1.68 m)	2.07"	10.0 lbs. (4.55 kg)	C-40
HV-235	35' (10.6 m)	68" (1.72 m)	2.22"	12.1 lbs. (5.5 kg)	C-40
HV-240	39'6" (12.0 m)	69" (1.75 m)	2.38"	14.4 lbs. (6.5 kg)	C-40

NOTE: See other side for component parts

*HV-208 can be stored in Cat. No. 06-185 cannister shown on cat. page G-4.

CAUTION: The products we supply are intended to be used and serviced only by professional personnel who have been trained in good work and safety practices relating to the use of this type of product. The information provided on the product does not cover every possible contingency to be encountered and it is not intended to be used as a substitute for adequate training and experience. If specific situations or questions arise regarding the use of the products or, if additional information is required, please or write the factory before proceeding.



HASTINGS
A WORLDWIDE SUPPLIER OF
Hot Line Tools & Equipment

A-a

A-a TELESCOPIC STICKS